



230qms e



For use before finishing with french polish, cellulose, polyurethane etc.

Wood must be clean and fine sanded. Mix with white spirit to a thin paste and rub hard across the grain with rag. Ensure all pores are filled, then wipe surface clean. Leave overnight to harden. If wood is to be stained, thin the filler with the required shade of Bustins Wood Dve and apoly as above.

Note: Use the Natural Grain Filler for light and bleached woods.

Fill holes and cracks with Rustins Wood Filler.

HEALTH & SAFETY

Contains Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics. May produce an allergic reaction. Flammable liquid and vapour. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from heat, not surfaces, sparks, open flames and other ignition sources. No smoking, Keep container tightly closed. Wear eve protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Store in a well-ventilated place. Keep cool. Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Warning

ık or contact us at

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, Loddon, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin, D13 Y860 Ireland Tel: +353 1 - 832 3300