

Rustins

Quick Dry

Small Job Gloss Paint



GLOSS Black



SMALL JOB GLOSS PAINT RANGE

CHOCOLATE

BUTTERCUP

OXFORD BLUE

POPPY

BUCKINGHAM
GREEN

DELPHINIUM

MAGNOLIA

CANDY PINK

BLACK

WHITE

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE
ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

STIR WELL BEFORE USE

A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.

Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10°C, in damp conditions or if rain is imminent.

Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Wear protective gloves and eye protection.


IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666



EU limit value for this product (cat A/I):
130g/l (2010).
This product contains max 74g/l VOC.



500ml e



For indoor & outdoor use

Quick Dry

Rustins

Small Job Gloss Paint



GLOSS
Chocolate



SMALL JOB GLOSS PAINT RANGE

CHOCOLATE

BUTTERCUP

OXFORD BLUE

POPPY

BUCKINGHAM GREEN

DELPHINIUM

MAGNOLIA

CANDY PINK

BLACK

WHITE

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

STIR WELL BEFORE USE

A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.

Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10°C, in damp conditions or if rain is imminent.

Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.


Wear protective gloves and eye protection. IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666



EU limit value for this product (cat AII): 130g/l (2010). This product contains max 74g/l VOC.



500ml e



For indoor & outdoor use

Quick Dry

Rustins

Small Job Gloss Paint



GLOSS
White



SMALL JOB GLOSS PAINT RANGE

CHOCOLATE

BUTTERCUP

OXFORD BLUE

POPPY

BUCKINGHAM GREEN

DELPHINIUM

MAGNOLIA

CANDY PINK

BLACK

WHITE

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

STIR WELL BEFORE USE

A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.

Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10°C, in damp conditions or if rain is imminent.

Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.


Wear protective gloves and eye protection. IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666



EU limit value for this product (cat AII): 130g/l (2010). This product contains max 74g/l VOC.



500ml e



For indoor & outdoor use

Quick Dry

Rustins

Small Job Gloss Paint



GLOSS
Poppy



SMALL JOB GLOSS PAINT RANGE

CHOCOLATE

BUTTERCUP

OXFORD BLUE

POPPY

BUCKINGHAM
GREEN

DELPHINIUM

MAGNOLIA

CANDY PINK

BLACK

WHITE

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE
ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

STIR WELL BEFORE USE

A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.

Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10°C, in damp conditions or if rain is imminent.

Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.


Wear protective gloves and eye protection.
IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666



EU limit value for this product (cat AII):
130g/l (2010).
This product contains max 74g/l VOC.



500ml e



For indoor & outdoor use

Quick Dry

Rustins

Small Job Gloss Paint



GLOSS
Oxford Blue



SMALL JOB GLOSS PAINT RANGE

CHOCOLATE

BUTTERCUP

OXFORD BLUE

POPPY

BUCKINGHAM GREEN

DELPHINIUM

MAGNOLIA

CANDY PINK

BLACK

WHITE

IMPORTANT: THESE COLOURS ARE AS CLOSE TO THE ACTUAL COLOUR AS THE PRINTING PROCESS PERMITS

STIR WELL BEFORE USE

A water based hardwearing paint for interior & exterior use that is touch dry in approximately 30 minutes. Suitable for use on wood and metal. Conforms to the Toys (Safety) Regulations 1995, BS:EN71 Part 3.

Preparation

The surface must be clean and free from wax and grease. If already painted, remove flaking paint by scraping or with Rustins Strypit Paint and Varnish Stripper. If applying to metal, remove any rust with a scraper or with Rustins Rust Remover and apply one coat of Quick Dry Rustins Red Oxide Metal Primer. It is not necessary to apply Knotting to knots on bare wood, but if the wood is very absorbent, a coat of Rustins Primer & Undercoat may be applied before applying the paint.

Application

STIR WELL BEFORE USE: Apply liberally and evenly with a synthetic fibre brush. Do not use below 10°C, in damp conditions or if rain is imminent.

Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after 2 hours.

Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains 5-chloro-2-methyl-2h-isothiazol-3-one (acticide fsn). May produce an allergic reaction.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.


Wear protective gloves and eye protection. IF ON SKIN: Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666



EU limit value for this product (cat AII): 130g/l (2010). This product contains max 74g/l VOC.



500ml e



For indoor & outdoor use