

Rustins
EST 1924

QUICK DRY Varnish

TOUCH DRY IN 30 MINUTES



Long lasting
wood protection

For all types of
interior wood

Clean brushes
in water

STIR WELL BEFORE USE

This low odour acrylic varnish is milky white whilst liquid but dries to a hard clear non-yellowing finish and is suitable for use on wood, cork, MDF and can be used as a sealer on concrete.

Preparation

The surface must be clean and free from wax, grease and dirt. Previously varnished surfaces should be rubbed down to provide a key, but if the old finish is not in good condition, remove it with Rustins Strypit Paint and Varnish Stripper. New wood should be sound and sanded smooth before application. Knotting should not be applied over knots.

Application

IMPORTANT: Stir well before use until there is no sediment on the bottom of the tin. If this is not done the varnish will dry with a gloss. Apply liberally across the grain using a synthetic fibre brush specially made for water-based finishes. Finish off by brushing lightly with the grain, taking care not to over-coat. The first coat may be thinned with up to 10% water in very warm conditions. If the first coat raises the grain, sand lightly with fine abrasive paper before applying a further coat. Three coats are recommended. This varnish is fully compatible with Rustins Quick Drying Coloured Varnish. The colour of bare wood can be changed before varnishing with Rustins Wood Dye.

Re-coating Time

The varnish will be touch dry in approximately 20 minutes depending upon the temperature and humidity and can be re-coated after a minimum of two hours.

Coverage

This tin will cover approximately 3.25 sq metres one coat depending on the absorbency of the wood to which the varnish is applied.

Cleaning

Remove as much varnish as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings.

Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

Important

Do not transfer the varnish into an unlacquered metal container. Use glass or polythene containers. If water splashes onto the surface within 3 days of application, it should be wiped off with a soft cloth.

HEALTH AND SAFETY Contains 5-chloro-2-methyl-2h-isothiazol-3-one. May produce an allergic reaction. Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Wear protective gloves. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

UFI: 616V-YRR8-SA1X-HSF3

Please refer to Product Data Sheet for full information at www.rustins.co.uk


For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX UK rustins@rustins.co.uk Tel: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT A/e):
130g/l (2010)

This product contains max 126g/l VOC



250ml e