

# **O**UICK **D**RYING RADIATOR

ENAMEL

HEAT RESISTANT TOUGH FINISH IDEAL TOUCH-UP

FOR FRIDGES ETC

**1** 



KEEPS WHITE LOW ODOUR **EXCELLENT** 

ON WOOD

The paint will be touch dry in approximately 30 minutes

- TOUCH DRY IN 30 MINUTES
- CLEAN BRUSHES IN WATER

## STIR WELL BEFORE USE

Rustins Radiator Enamel is based on a special nonyellowing acrylic resin emulsion pigmented with titanium oxide. Heat-resistant to 105°C. This produces a brilliant white finish that does not vellow on hot radiators. It is also excellent on wood which must be undercoated. It can also be used as a touch-up paint on white equipment such as refrigerators. Do not use at temperatures below 10°C or in conditions of high humidity.

## Preparation

Previously painted radiators must be clean and free from flaking paint and rust. Clean with White Spirit. Rustins Surface Cleaner or Sugar soap. If existing paint is not white, apply a coat of Rustins Quick Drying Primer & Undercoat. Bare metal should be primed with Rustins Red Oxide Primer. Remove rust before priming with Rustins Rust Remover.

## Application

Stir well before use. Apply liberally and evenly with a synthetic fibre brush. Allow radiators to cool before painting. Radiators can be used between coats if necessary

## Re-coating Time

depending on temperature and humidity and can be recoated after four hours.

## Coverage

This tin will cover approximately 3 sq.m in 1 coat depending on the absorbency of the surface.

## Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

## Storage

Store in a cool dry place with the lid tightly closed. Protect from frost

#### HEALTH AND SAFETY

Contains texanol, a mixture of: 5-chloro-2methyl-2h-isothiazol-3-one (ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. Warning Keep out of reach of children. Wear protective gloves and eve protection Do not get in eyes, on skin, or on clothing IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Bustins Ltd. Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Tel: +44 (0)20 8450 4666



EU limit value for this product (cat A/i): 140a/l (2010). This product contains max 78g/l VOC



