



Quick Dry

# Rustins

## Stain Blocker & Multi-Surface Primer

Seals all stains that bleed through to spoil top coat

Seals difficult stains such as:

Bitumen	Nicotine
Crayon	Rust
Dry water	Soot
Graffiti	Tannin



For indoor & outdoor use

Excellent adhesion to:

Ceramic tiles	Melamine
Concrete	Mortar
Drywall	Paint
Glass	Plasterboard
MDF	Wood

Always test a small area for compatibility first

A water based matt white stain blocker for interior and exterior use, with excellent adhesion to wood, plaster and previously painted surfaces. It will seal all stains that may bleed through and discolour paint.

As a primer, it provides excellent adhesion to ceramic tiles, glass, and melamine.

When dry, it can be painted with any type of paint and undercoat. It can be applied over asphalt, bitumen, crayon, creosote, graffiti, nicotine, rust, soot, tannin and water stains.

### Preparation

The surface must be clean and free from wax and grease. Clean with water and detergent, rinsing with clean water. Remove any loose paint by scraping or sanding.

### Application

Stir well before use. Apply liberally & evenly with a brush or roller using a brush with synthetic fibres manufactured for use with water-based paints. Do not thin. Do not use at temperatures below 10°C or in conditions of high humidity.

### Re-coating Time

Surface dry in approximately 30 minutes, depending on temperature and humidity. Some stains may require a second coat, which can be applied two hours after the first coat has dried.

### Coverage

1 litre will cover approximately 12 sq.m in 1 coat depending on the absorbency of the surface.

### Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

### Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

### HEALTH AND SAFETY


Contains a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Wear protective gloves and eye protection. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666



EU Limit value for this product (CAT A/g): 30g/l (2010)  
This product contains max 15 g/l VOC



500ml e