

Rustins

Yacht Varnish Gloss

The finest
all weather
wood finish

UV
protection



Preparation: The surface must be clean, smooth and free from dust. If applying over existing varnish, it should be lightly sanded to provide a key. If flaking or cracking, it should be stripped using Rustins Strypit Paint and Varnish Stripper.

Application: Using a good quality brush, apply evenly. When applying to new wood, thin with 25% white spirit by volume. Previously varnished surfaces if intact, should be cleaned with white spirit or Rustins Surface cleaner and steel wool to ensure the surface is clean and free from wax and grease. Weather-stained wood can be bleached with Rustins Wood Bleach. The thickness of the varnish film is important and for good durability, at least three coats should be applied. Do not use below 10°C, in damp conditions or if rain is imminent.

Recoating: Further coats can be applied once the previous coat is hard dry. This will usually be after 12 hours depending on the temperature and humidity at the time of application.

Coverage: 1 litre will cover approximately 13 sq m in one coat depending on the absorbency of the surface.

Clean Brushes: Clean brushes whilst wet using Rustins Brush Cleaner or white spirit. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention): Some authorities have special facilities for disposal of waste paints and varnishes. Do not empty into drains, water courses or the sea.

HEALTH & SAFETY

Flammable liquid and vapour. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour/ spray. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Use only outdoors or in a well-ventilated area. Store in a well-ventilated place. Keep cool.

Contains HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics.


UFI: 4198-H40C-621P-H742

Please refer to Product Data Sheet for full information at www.rustins.co.uk



WARNING

EU limit value for this product (cat A/e):
400g/l (2010).
This product contains max 395g/l VOC



For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX UK rustins@rustins.co.uk Tel: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland.
Tel: +353 1 - 832 3300

2.5 Litre



Yacht Varnish Satin

The finest
all weather
wood finish



Made in UK



Stir before use until there is no sediment at the bottom of the tin. If not stirred the varnish may dry to a gloss.

Preparation: The surface must be clean, smooth and free from dust. If applying over existing varnish, it should be lightly sanded to provide a key. If flaking or cracking, it should be stripped using Rustins Strypit Paint and Varnish Stripper.

Application: Using a good quality brush, apply evenly. When applying to new wood, thin with 25% white spirit by volume. Previously varnished surfaces if intact, should be cleaned with white spirit or Rustins Surface cleaner and steel wool to ensure the surface is clean and free from wax and grease. Weather-stained wood can be bleached with Rustins Wood Bleach. The thickness of the varnish film is important and for good durability, at least three coats should be applied. It is better to apply during warm, dry weather.

Recoating: Further coats can be applied once the previous coat is hard dry. This will usually be after 12 hours depending on the temperature and humidity at the time of application.

Coverage: 1 litre will cover approximately 13 sq m in one coat depending on the absorbency of the surface.

Clean Brushes: Clean brushes whilst wet using Rustins Brush Cleaner or white spirit. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention): Some authorities have special facilities for disposal of waste paints and varnishes. Do not empty into drains, water courses or the sea.

HEALTH & SAFETY

Flammable liquid and vapour. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour/ spray. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Use only outdoors or in a well-ventilated area. Store in a well-ventilated place. Keep cool.

Contains HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics


UFI: 4198-H40C-621P-H742

Please refer to Product Data Sheet for full information at www.rustins.co.uk



WARNING

EU limit value for this product (cat A/e):
400g/l (2010).
This product contains max 395g/l VOC



For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX UK rustins@rustins.co.uk Tel: +44 (0)20 8450 4666

2.5 Litre

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland.
Tel: +353 1 - 832 3300

