

- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

500ml e

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-DOAQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**



**SATIN  
CLEAR**

**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-DOAQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)  
This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**



**GLOSS  
CLEAR**

**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use.

Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-D0AQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**

**MATT  
CLEAR**



**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-D0AQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**



**SATIN  
ANTIQUÉ PINE**

**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-D0AQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**



**SATIN  
DARK OAK**

**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-DOAQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)  
This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**



**SATIN  
EBONY**

**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-D0AQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**

**SATIN  
MAHOGANY**



**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

500ml e

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-D0AQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

# Rustins

## QUICK DRY POLYURETHANE VARNISH

EXTRA TOUGH



SATIN OAK

FOR INTERIOR & EXTERIOR USE



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.





- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

500ml e

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-D0AQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

# Rustins

## QUICK DRY POLYURETHANE VARNISH

EXTRA TOUGH



SATIN PINE

FOR INTERIOR & EXTERIOR USE



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-DOAQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**



**SATIN  
TEAK**

**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



- Long lasting wood protection
- For all types of interior and exterior wood
- Low odour & non toxic
- Enhances the beauty of wood
- Resists alcohol & boiling water
- Clean brushes in water

**For use on:**

- Window Ledges
- Tables & Chairs
- Doors
- Shelving
- Cupboards
- Bannisters

**500ml e**

**HEALTH & SAFETY**

Contains Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol. May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust/fume/gas/ mist/vapours/spray. Wear eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: X300-DOAQ-900E-2KRH

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 126g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Warning

**Rustins**

**QUICK DRY  
POLYURETHANE  
VARNISH**

**EXTRA  
TOUGH**



**SATIN  
WALNUT**

**FOR INTERIOR & EXTERIOR USE**



**STIR WELL BEFORE USE**

A water-based, non-yellowing polyurethane varnish that is tough and durable and will resist cracking, peeling and blistering. Can be used on bare wood, hardboard, MDF, unsealed cork. For interior and exterior use.

**Preparation**

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller. Rustins Wood Dye may be applied to bare wood prior to varnishing.

**Application**

Stir well before use or it will dry to a gloss finish. Use a synthetic brush and apply liberally with a full brush finishing with the grain. Externally the first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely. Three coats is recommended. Lightly sand after first coat if there is raising of the grain. Note: with every successive coat of coloured varnish the finish will become darker, but may then be overcoated with clear varnish to maintain a satisfactory shade whilst achieving the total coating thickness.

**Re-coating Time**

Further coats can be applied once the previous coat is dry. This will be touch dry in 30 minutes and can be re-coated in approximately 2 hours depending on the temperature and humidity at the time of application.

**Coverage**

1 litre will cover approximately 12-15 sq.m in 1 coat depending on the absorbency of the surface.

**Cleaning**

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

**Disposal (pollution prevention)**

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

**Maintenance**

If used outdoors: re-coat every 2 to 3 years depending upon the severity of exposure. Clean with a mild detergent solution and lightly sand to provide key.

**Storage**

Store upright in a cool dry place between 10-35°C with the lid tightly closed.

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.

