

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PLASTIC FLOOR COATING

Product code: PCFL

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd
Waterloo Road
Cricklewood
London
NW2 7TX
United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36; Sens.: R43

Classification under CLP: Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; -: EUH208

Most important adverse effects: Highly flammable. Irritating to eyes. May cause sensitisation by skin contact.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains methyl ethyl ketoxime. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS05: Corrosion

GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 2

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor.
P321: Specific treatment (see instructions on this label).
P370+378: In case of fire: Use carbon dioxide for extinction.

Label elements under CHIP:

Hazard symbols: Highly flammable.
Irritant.



Risk phrases: R11: Highly flammable.
R36: Irritating to eyes.
R43: May cause sensitisation by skin contact.

Safety phrases: S24: Avoid contact with skin.
S37: Wear suitable gloves.

Precautionary phrases: Contains formaldehyde...100%, methyl ethyl ketoxime. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-578-6	64-17-5	F: R11 Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%

ISOBUTANOL

201-148-0	78-83-1	-: R10; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	-------------------------------------	---	-------

[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 3

PROPAN-2-OL

200-661-7	67-63-0	F: R11; Xi: R36; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	1-10%
-----------	---------	-------------------------	--	-------

XYLENE

215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	-----------------------------	--	-------

WHITE SPIRIT

265-185-4	64742-82-1	-: R10; N: R51/53; Xn: R65; -: R66; -: R66	-	<1%
-----------	------------	---	---	-----

METHANOL

200-659-6	67-56-1	F: R11; T: R23/24/25; T: R39/23/24/25	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%
-----------	---------	--	---	-----

FORMALDEHYDE

200-001-8	50-00-0	T: R23/24/25; C: R34; Xn: R40; Sens.: R43	Carc. 2: H351; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; Skin Corr. 1B: H314; Skin Sens. 1: H317	<1%
-----------	---------	--	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for breathing and apply artificial respiration if necessary.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Irritation. Repeated or prolonged contact may cause defatting of the skin leading to irritation and dermatitis.

Eye contact: Irritation. May cause corrosive burns.

Ingestion: Nausea, vomiting and dizziness. Harmful, causing internal irritation.

Inhalation: Irritation of the respiratory tract. Drowsiness, nausea and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder. Do not use water.

[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Eliminate all sources of ignition. If outside do not approach from downwind. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use. Exclude sources of heat, sparks and open flame. Earth any equipment used in handling. Use non-sparking tools. The Manual Handling Operations Regulations may apply to the handling of containers of this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from direct sunlight. Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non-sparking tools should be used. Take precautionary measures to prevent product spills into drains, the ground or waters. Further guidance is contained in the HSE guidance note Storage of Flammable Liquids in Containers.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel containers.

[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 5

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m ³	-	-	-

ISOBUTANOL

UK	154 mg/m ³	231 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

PROPAN-2-OL

UK	999 mg/m ³	1250 mg/m ³	-	-
----	-----------------------	------------------------	---	---

XYLENE

UK	220 mg/m ³	441 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

METHANOL

UK	266 mg/m ³	333 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

FORMALDEHYDE...100%

UK	2.5 mg/m ³	2.5 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see Respiratory protection below).

Respiratory protection: If there is a risk of exposure to high vapour concentrations, use respiratory protective equipment. All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Hand protection: Wear Nitrile gloves. Wash hands thoroughly after handling chemicals.

Eye protection: Eye protection designed to protect against liquid splashes should be worn. Ensure eye bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 6

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Clear (pale amber).

Odour: Pungent

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: 80

Flash point°C: 16

Relative density: 0.976@20 C

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion may emit toxic fumes of carbon dioxide, carbon monoxide, formaldehyde, oxides of nitrogen and hydrogen cyanide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 7

ISOBUTANOL

IVN	MUS	LD50	417	mg/kg
IVN	RAT	LD50	340	mg/kg
ORL	RAT	LD50	2460	mg/kg

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

FORMALDEHYDE...100%

ORL	MUS	LD50	42	mg/kg
ORL	RAT	LD50	100	mg/kg
SCU	RAT	LD50	420	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Irritation. Repeated or prolonged contact may cause defatting of the skin leading to irritation and dermatitis.

Eye contact: Irritation. May cause corrosive burns.

Ingestion: Nausea, vomiting and dizziness. Harmful, causing internal irritation.

Inhalation: Irritation of the respiratory tract. Drowsiness, nausea and dizziness.

Section 12: Ecological information

[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 8

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: There is no data available on the product itself.

12.3. Bioaccumulative potential

Bioaccumulative potential: There is no data available on the product itself.

12.4. Mobility in soil

Mobility: Partially volatile. Immiscible in water. Partly evaporates from water or soil surfaces. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

[cont...]

SAFETY DATA SHEET

PLASTIC FLOOR COATING

Page: 9

15.2. Chemical Safety Assessment

Chemical safety assessment: Safety Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H301: Toxic if swallowed.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
R10: Flammable.
R11: Highly flammable.
R20/21: Harmful by inhalation and in contact with skin.
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.
R34: Causes burns.
R36: Irritating to eyes.
R37/38: Irritating to respiratory system and skin.
R38: Irritating to skin.
R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R40: Limited evidence of a carcinogenic effect.

[cont...]

SAFETY DATA SHEET
PLASTIC FLOOR COATING

Page: 10

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: Even after washing the rags must never be crumpled into a ball but spread out and disposed of. Use synthetic fibre cloths where possible as natural fibres, especially cotton, increase the chances of spontaneous combustion. This data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

[final page]