

## **Expert finishes for wood and metal**

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

June 2019

## PRODUCT DATA SHEET

Product	Quick Dry Small Job Gloss & Satin Paint
Туре	An acrylic emulsion based paint. The finish produced is tough, durable and resistant to oil and water.
Intended Use	A decorative coating for application over <b>Rustins Quick Drying Primer Undercoat</b> or over existing paints and varnishes on wood and metal. For interior and exterior use.
Special Features	Available in 10 attractive shades: Poppy (Red), Buttercup, Oxford Blue, Buckingham Green, Delphinium, Chocolate, Candy Pink, Magnolia, Black & White Conforms to the Toy Safety Regulations BS EN 71 Part 3 1995.
Preparation	The surface must be clean, smooth, sound, dry and free from wax, dust and contaminants. If the wood or metal surface is bare, apply the appropriate primer and undercoat before painting. On metal use Rustin's Red Oxide Metal Primer. On wood use Rustin's Quick Drying Primer & Undercoat. Prior to painting, existing coated surfaces should be cleaned with Rustin's Surface Cleaner, or Rustins Sugar Soap and sanded lightly to provide a key, prior to painting. Cracks may be filled with Rustin's Wood filler. Undercoat may be applied if required.
Application	Apply light, even coats using a good quality brush for water-based coatings.
Coats	1 coat is sufficient but a second coat may be applied if required. It is better to apply two light coats rather than one heavy coat.
Drying Time	Touch dry within 30 minutes, depending on the temperature and humidity.
Re-coating Time	3-4 hours, depending on the temperature and humidity.
Application Temp.	Ideally, 15-25°C. Do not use below 10°C or in conditions of high humidity or if rain is imminent.
Coverage	12-15 sq.metres per litre depending on the absorbency of the surface.
Maintenance	The surface may be cleaned with a mild detergent solution or White Spirit as necessary.  Worn areas may be re-coated once cleaned and lightly sanded to provide a key.
Compatibility	Compatible over most types of undercoat. Can be applied over top coats once thoroughly cleaned and lightly sanded to provide a key.
Settlement	STIR WELL BEFORE USE
Shelf-life/Storage	Many years if stored in original, tightly closed container in cool dry conditions.
Hazards	Keep out of reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser A full Safety Data Sheet is available upon request or on <a href="https://www.rustins.co.uk">www.rustins.co.uk</a>
Clean-Up	Remove excess product from brushes before cleaning. Clean brushes whilst wet with water. Hard brushes can be cleaned with <b>Rustins Brush Restorer</b> .
Sizes	250 mls and 500mls