

October 2016

PRODUCT DATA SHEET

Product	Quick Dry Stain Blocker & Multi-Surface Primer
Type	Quick drying water based matt white primer with excellent adhesion to a wide range of surfaces.
Intended Use	Can be used on ceramic tiles, concrete, mortar, melamine, drywall, glass, paint, MDF, wood and plasterboard.
Special Features	Low odour. Non-yellowing on ageing. Quick-drying. Wash brushes in water. When dry can be painted over with many types of paints and undercoat.
Preparation	The surface must be dry and free from, dust and contaminants.
Application	Application Using a synthetic brush or varnish roller, apply evenly and liberally.
Coats	Apply 3 liberal coats according to the coverage rate. More absorbent surfaces or commercial premises may require 4 coats.
Drying Time	Touch dry within 20 minutes depending on the temperature and humidity.
Re-coating Time	2 hours, depending on the temperature and humidity.
Application Temp.	Ideally 15-25°C. Do not use below 10°C, or in conditions of high humidity.
Coverage	9-10 sq. metres/litre per coat, depending on the absorbency of the surface.
Maintenance	N/A
Compatibility	When dry can be painted over with undercoat and many types of paints.
Settlement	STIR WELL BEFORE AND DURING USE.
Shelf-life/Storage	Many years if stored in original, tightly closed container in normal conditions. Protect from frost.
Hazards	Non-flammable. Flash point: Nil. Avoid contact with eyes, skin and clothing. A Full Safety Data Sheet is available upon request or on www.rustins.co.uk
Clean-Up	With water whilst still wet. If dried-on, clean equipment & brushes with Rustin's Brush Restorer .
Sizes	250ml 500ml 1Litre